



HTDL2-3Y INNO - RT



Also compliant with: CE, FCC, ISED



RF TECHNOLOGY

Wireless Connection

Our loggers can send the signal within 700 meters in free space



NFC TECHNOLOGY

Access to Data at a Glance

Quickly access data history using any NFC-enabled device



HUMIDITY SENSOR

Keep Humidity Level in Check

Get an alert in case the humidity level crosses specified thresholds



RESISTANCE

Save Money on Replacements

The loggers are resistant to weather conditions and mechanical damage



SMALL SIZE

Size Easy-to-Integrate

Directly integrate the logger inside any kind of container or pallet



SECURITY

Prevent from Data Manipulation

Thanks to the proprietary UDP protocol with AES cryptography

HTDL2-3Y INNO - RT


Real-time temperature & humidity
monitoring with ease



Temperature range	-30°C to +70°C / 0% to 100%
Accuracy	+/- 0.2°C from 0°C to +30°C (typically) +/- 0.5°C for the rest of the range
Humidity accuracy	+/- 2% from 20% to 80% (typically)
Validity	3 years
RF frequency	869.0 MHz for Europe 920.9 MHz for USA, Asia, Brasil, etc.
Radio range	Up to 700m in free space
Resolution	0.1°C
Intervals	From 1 min to 2 hours (custom set up)
Memory	5,000 records with automatic rollover
Power supply	Internal battery
IP	44
Housing material	Polycarbonate
Dimensions	103mm x 60mm x 12mm

EQUIPMENT NEEDED

FOR RF



Ethernet / 2G

FOR NFC



NFC Reader

OR



Android phone / iPhone